

# TSG geared trolley

- ▶ Up to 30,000 kg load capacity
- ▶ Lightweight and compact design
- ▶ Fall protection device and rubber bumpers
- ▶ Extensive range of flange widths
- ▶ Heat-treated wheels
- ▶ Connector C for rigid suspension and / or hook suspension up to 5,000 kg

## Options

- ▶ Connector E for ER2 electric chain hoist
- ▶ W30 flange width extender

## Technical data

Type	Load capacity kg	Shaft	Flange width mm	Connector	Hand chain m	Ø Hand chain mm	Curve radius min. mm	Weight kg
TSG	125	Standard	58 - 163	C	3.0	5.0 x 25.0	1,350 - 1,400	13.5
TSG	125	W30	164 - 305	C	3.0	5.0 x 25.0	1,350 - 1,400	13.5
TSG	250	Standard	58 - 163	C	3.0	5.0 x 25.0	1,350 - 1,400	13.5
TSG	250	W30	164 - 305	C	3.0	5.0 x 25.0	1,350 - 1,400	13.5
TSG	500	Standard	58 - 163	C	3.0	5.0 x 25.0	1,350 - 1,400	13.5
TSG	500	W30	164 - 305	C	3.0	5.0 x 25.0	1,350 - 1,400	13.5
TSG	1,000	Standard	58 - 163	C	3.0	5.0 x 25.0	1,350 - 1,400	13.5
TSG	1,000	W30	164 - 305	C	3.0	5.0 x 25.0	1,350 - 1,400	13.5
TSG	1,500	Standard	82 - 204	C	3.0	5.0 x 25.0	1,600	20.0
TSG	1,500	W30	205 - 305	C	3.0	5.0 x 25.0	1,600	20.0
TSG	2,000	Standard	82 - 204	C	3.0	5.0 x 25.0	1,600	21.0
TSG	2,000	W30	205 - 305	C	3.0	5.0 x 25.0	1,600	21.0
TSG	2,500	Standard	82 - 204	C	3.0	5.0 x 25.0	1,800	30.0
TSG	2,500	W30	205 - 305	C	3.0	5.0 x 25.0	1,800	30.0
TSG	3,000	Standard	82 - 204	C	3.0	5.0 x 25.0	1,800	30.0
TSG	3,000	W30	205 - 305	C	3.0	5.0 x 25.0	1,800	30.0
TSG	5,000	Standard	100 - 204	C	3.0	5.0 x 25.0	2,400	60.0
TSG	5,000	W30	205 - 305	C	3.0	5.0 x 25.0	2,400	60.0
TSG	7,500	Standard	150 - 220	-	3.0	5.0 x 25.0	3,000 - 3,100	115.0
TSG	7,500	W30	221 - 305	-	3.0	5.0 x 25.0	3,000 - 3,100	115.0
TSG	10,000	Standard	150 - 220	-	3.0	5.0 x 25.0	3,000 - 3,100	115.0
TSG	10,000	W30	221 - 305	-	3.0	5.0 x 25.0	3,000 - 3,100	115.0
TSG	15,000	Standard	150 - 220	-	3.0	5.0 x 25.0	-	271.0
TSG	15,000	W30	221 - 305	-	3.0	5.0 x 25.0	-	271.0
TSG	20,000	Standard	150 - 220	-	3.0	5.0 x 25.0	-	271.0
TSG	20,000	W30	221 - 305	-	3.0	5.0 x 25.0	-	271.0
TSG	30,000	Standard	175 and 190	-	3.0	5.0 x 25.0	-	450.0



**TSG for ER2 electric chain hoist with connector E**



**TSG geared trolley 125 kg to 3,000 kg**



**TSG geared trolley 5,000 kg to 30,000 kg**



**TSG  
with connector C  
for hand chain block**